



AFCO Systems Basic Power Strip Specifications

Part No. GB1-C30-C24D6-D



AC Rating Volts	250
AC Rating Amps	30
AC Rating Watts	7500 de-rated to 6000
AC Rating Frequency	50/60 Hz
Over Current Protection	(2) 20 AMP Double Pole Magnetic Breakers
Power Switch	Breaker/Switch Combination
Power Cable AWG	10/3
Cord Length	10 ft
Plug Type	NEMA L6-30P Twistlock Plug
Receptacle Type	IEC320 C-13
Receptacles on Face	24
Quantity per Breaker and/or Phase Combination	12
Receptacle Style	Grouped
Maximum Output per Receptacle	15A per receptacle bank
Receptacle Type	IEC320 C-19
Receptacles on Face	6
Quantity per Breaker and/or Phase Combination	2
Receptacle Style	Individual
Maximum Output per Receptacle	20A
Heavy Steel - Black Powder Coat	Yes
Made in the USA	Yes
Configuration	66" Vertical Rackmount
Toolless Mounting Hardware	Yes - 61.25" Center to Center Spacing
RoHS Compliant	RoHS Compliant
Product Warranty	Three year
Certification/Agency Approvals	UL & c-UL Listed 60950
Chassis Dimensions (LxWxD)	66.25" x 2.0" x 3.5" (1.44" doghouse)
Unit Weight	17 lbs.
Monitoring	No Meter

AFCO Systems...partnered with you through the lifecycle of your datacenter.

