



AFCO Systems Metered Power Strip Specifications

Part No. GM1-C20-C24D6-D

| | |
|---------------------------------|--|
| AC Rating Volts | 250 |
| AC Rating Amps | 20 |
| AC Rating Watts | 5000 (20 X 250) |
| AC Rating Frequency | 50/60 Hz |
| Over Current Protection | None |
| Power Switch | None |
| Power Cable AWG | 12/3 |
| Cord Length | 10 ft |
| Plug Type | NEMA L6-20P Twistlock Plug |
| Total receptacles | 30 |
| Receptacle Type | IEC320 C-13 |
| Receptacles on Face | 24 |
| Receptacle Style | Grouped |
| Maximum Output per Receptacle | 15A per receptacle bank |
| Receptacle Type | IEC320 C-19 |
| Receptacles on Face | 6 |
| Receptacle Style | Individual |
| Maximum Output per Receptacle | 20A |
| Heavy Steel - Black Powder Coat | Yes |
| Configuration | 66" Vertical Rackmount |
| Full Length Bracket | Yes |
| Toolless mounting hardware | Yes – 61.25" & 64.75" Center to Center Spacing |
| Product Warranty | Three Year |
| Certification/Agency Approvals | UL & c-UL Listed 60950 |
| Chassis Dimensions (LxWxD) | 66.25" x 2.0" x 3.5" (1.44" doghouse) |
| Unit Weight | 17 lbs. |
| Monitoring | Current Meter Local - Non Scrolling Digital RMS Current Meter ±2% Accuracy with Full Scale 60 Hz sine wave input |

AFCO Systems...partnered with you through the lifecycle of your datacenter.

