



AFCO Systems Metered Power Strip Specifications

Part No. GM1-D30-C24D6-F



AC Rating Volts	208
AC Rating Amps	30 x 3 Phase WYE
AC Rating Watts	10800 de-rated to 8640
AC Rating Frequency	50/60 Hz
Over Current Protection	(3) 20 AMP Double Pole Magnetic Breakers
Power Switch	Breaker/Switch Combination
Power Cable AWG	10/5
Cord Length	10 ft
Plug Type	NEMA L21-30P Twistlock Plug
Receptacle Type	IEC320 C-13
Receptacles on Face	24
Quantity per Breaker and/or Phase Combination	8
Receptacle Style	Grouped
Maximum Output per Receptacle	15A per receptacle bank
Receptacle Type	IEC320 C-19
Receptacles on Face	6
Quantity per Breaker and/or Phase Combination	2
Receptacle Style	Individual
Maximum Output per Receptacle	20A
Heavy Steel - Black Powder Coat	Yes
Made in the USA	Yes
Configuration	66" Vertical Rackmount
Tool less mounting hardware	Yes – 61.25" Center to Center Spacing
RoHS Compliant	RoHS Compliant
Product Warranty	Three Year
Certification/Agency Approvals	UL & c-UL Listed 60950
Chassis Dimensions (LxWxD)	66.25" x 2.0" x 3.5" (1.44" doghouse)
Unit Weight	17 lbs.
Monitoring	Current Meter Local - 3 Phase Scrolling Digital RMS Scrolling Current Meter $\pm 2\%$ Accuracy with Full Scale 60 Hz sine wave input

AFCO Systems...partnered with you through the lifecycle of your datacenter.

