



AFCO Systems Metered Power Strip Specifications

Part No. GM1-E20-C24D6-F

AC Rating Volts	120
AC Rating Amps	20 x 3 Phase WYE
AC Rating Watts	7200 de-rated to 5760
AC Rating Frequency	50/60 Hz
Over Current Protection	None
Power Switch	No
Power Cable AWG	12/5
Cord Length	10 ft
Plug Type	NEMA L21-20P Twistlock Plug
Receptacle Type	IEC320 C-13
Receptacles on Face	24
Quantity per Breaker and/or Phase Combination	8
Receptacle Style	Grouped
Maximum Output per Receptacle	15A per receptacle bank
Receptacle Type	IEC320 C-19
Receptacles on Face	6
Quantity per Breaker and/or Phase Combination	2
Receptacle Style	Individual
Maximum Output per Receptacle	20A
Heavy Steel - Black Powder Coat	Yes
Made in the USA	Yes
Configuration	66" Vertical Rackmount
Toolless Mounting Hardware	Yes - 61.25" Center to Center Spacing
Product Warranty	Three Year
Certification/Agency Approvals	UL & c-UL Listed 60950
Chassis Dimensions (LxWxD)	66.25" x 2.0" x 2.0"
Unit Weight	13 lbs.
Monitoring	Current Meter Local - 3 Phase Scrolling Digital RMS Scrolling Current Meter ±2% Accuracy with Full Scale 60 Hz sine wave input

AFCO Systems...partnered with you through the lifecycle of your datacenter.

