



# AFCO Systems Metered Power Strip Specifications

Part No. GM1-E30-C24D6-F

AC Rating Volts	120
AC Rating Amps	30 x 3 Phase WYE
AC Rating Watts	10800 de-rated to 8640
AC Rating Frequency	50/60 Hz
Over Current Protection	(3) 20 AMP Double Pole Magnetic Breakers
Power Switch	Breaker/Switch Combination
Power Cable AWG	10/5
Cord Length	10 ft
Plug Type	NEMA L21-30P Twistlock Plug
Receptacle Combined Total Quantity	8
Receptacle Type	IEC320 C-13
Receptacles on Face	24
Quantity per Breaker and/or Phase Combination	8
Receptacle Style	Grouped
Maximum Output per Receptacle	15A per receptacle bank
Receptacle Type	IEC320 C-19
Receptacles on Face	6
Quantity per Breaker and/or Phase Combination	2
Receptacle Style	Individual
Maximum Output per Receptacle	20A
Monitoring	Current Meter Local - 3 Phase Scrolling  Digital RMS Scrolling Current Meter $\pm 2\%$ Accuracy with Full Scale 60 Hz sine wave input
Heavy Steel - Black Powder Coat	Yes
Made in the USA	Yes
Configuration	66" Vertical Rackmount
Toolless Mounting Hardware	61.25" and 64.75" Center to Center Spacing
RoHS Compliant	RoHS Compliant
Product Warranty	Three Year
Certification/Agency Approvals	UL & c-UL Listed 60950
Chassis Dimensions (LxWxD)	66.25" x 2.0" x 3.5" (1.44" doghouse)
Unit Weight	17 lbs.

*AFCO Systems...partnered with you through the lifecycle of your datacenter.*

